


# TLM-120 Thulium CW Fiber Laser Module

#### **NEW PRODUCT**





## **Applications**

- ▶ Medical Treatment
- ► Medical Surgery
- ▶ Plastic Materials Processing
- ► Other Non-metal Materials Processing
- ▶ Solid State IR Laser Pumping
- ▶ Pollution Control



### **Features**

- ▶ Compact Size
- ► High Wall-plug Efficiency
- ▶ Beam Quality M² < 1.1 for Single-mode Version
- Wide Selection of Wavelengths
- ► Advantage over CO<sub>2</sub> & Ho:YAG
- ➤ Cost-effective, Compact OEM Solution

**IPG's new Thulium Continuous Wave (CW) Fiber Laser Modules** are available in air-cooled units, 10-50 W or water-cooled modules, 50-120 W. These compact modules can be purchased for single-mode or multi-mode operation with wavelength range of 1900-2050 nm. IPG's Thulium modules are attractively priced for OEM's and integrators and serve a wide range of medical, materials processing and laser pumping applications.



# TLM-120

### Thulium CW Fiber Laser Module


### **Optical Characteristics**

Central Wavelength Range <sup>1</sup> , nm	1900-2000, typ. 1940
Linewidth FWHM, nm	0.7
Mode of Operation	CW/ Modulated
Modulation Frequency, kHz	up to 1
Average Power, W	120
Power Tunability, %	10-100
Power Stability <sup>2</sup> , %	±1
Optical Noise <sup>3</sup> , % RMS	1
Fiber Options	Single-mode, 50 μm, 100 μm
Beam Quality (Single-mode), M <sup>2</sup>	TEM <sub>00,</sub> , <1.1

<sup>&</sup>lt;sup>1</sup>Custom central wavelengths are available upon request

### General Characteristics

Module Dimensions, mm	355 x 407 x 53
Cooling	Water-cooled
Supply Voltage, VDC	48
Power Consumption, W	1200



+1 (508) 373-1100

sales.us@ipgphotonics.com

### www.ipgphotonics.com

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind IPG only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with use of a product or its application. IPG, IPG Photonics, The Power to Transform and IPG Photonics' logo are trademarks of IPG Photonics Corporation. © 2012-2014 IPG Photonics Corporation. All rights reserved.



2

■ The Power to Transform®

<sup>&</sup>lt;sup>2</sup> Over 4 hours, T=const

<sup>&</sup>lt;sup>3</sup> 10 kHz - 20 MHz