



MRL-S -671 /1~200mW



LD PUMPED ALL-SOLID-STATE RED LASER

All solid state laser at 671nm is made features of ultra compact, small size, wide operating temperature, good sealing, long lifetime, low cost and easy operating, working under the pressure of 0.02kPa, which is widely used in measurement, spectrum analysis, and laser lighting show, etc.



SPECIFICATIONS

Model	MGL-S-671-A(Harsh condition)	MGL-S-671-B (Normal condition)
Wavelength (nm)	671±1	
Operating mode	CW	
Output power (mW)	>1, 5, 10, 20, ..., 200	
Power stability (rms, over 4 hours)	<3%,<5%	
Transverse mode	TEM ₀₀	
M ² factor	<1.2	
Beam diameter at the aperture(1/e ² ,mm)	0.7±0.05	
Beam divergence, full angle (mrad)	<1.5	
Polarization ratio	>100:1 Horizontal±5 degree (Vertical Optional)	
Pointing stability after warm-up (mrad)	<0.05	
Pointing stability Over Temp. (μrad/°C)	<8	
Warm-up time (minutes)	<5	
Beam height from base plate (mm)	19	
Power Consumption(W)	<30	
Shock Tolerance(6ms)	7g laterally,15g vertically	
IP Rating	IP67	IP65
Power supply(90-264VAC or 5VDC)	PSU-H-FDA	PSU-III-LED PSU-III-FDA PSU-III-OEM-97
Operating temperature (°C)	0-60	10-35
Max. Heat Dissipation of Head(W)	10W@50°C	4W@25°C
Modulation	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option	
Expected lifetime (hours)	10000	
Warranty	1 year	



MxL-S-671	PSU-III-LED	PSU-III-FDA	PSU-III-OEM-97
 100 (L) × 40 (W) × 40(H) mm ³ , 0.41kg	 153 (L) × 155(W) × 92 (H) mm ³ , 1.5kg	 133 (L) × 130(W) × 62.2 (H) mm ³ , 1.2kg	 94(L)×75(W)×49(H)mm3, 0.23kg