


RPB Fiber Optic Raman Probe

Low-cost Sampling Solution

The RPB fiber optic probe is a breakthrough for routine laboratory Raman spectroscopy. A modified design based upon the patented RamanProbeTM optical layout has resulted in drastic cost-reduction with limited performance tradeoff. It is the clear Cost/Performance winner among laboratory Raman sampling probes.

The RPB is available for three excitation wavelengths: 785, 633, and 532 nm and can be directly coupled to a most spectrograph designs. Optical filtering of 106 offers efficient attenuation of the Rayleigh line for background-



free spectra. The probe is lightweight and compact, and has a manual safety shutter to shield the user from laser light. As with our standard RamanProbeTM, the RPB can be used with the compact sample holder for routine measurement of liquids and solids. Custom configurations are available for high-volume applications.

Features and Specifications

Sampling Head	Anodized aluminum probe, $4.2" \times 1.5" \times 0.5"$ (107 x 38 x 12.7 mm), with 1.5" (38 mm) long non-immersible, stainless-steel probe tip
Spectral Range	300 - 3900 cm ⁻¹ (Stokes), depending upon spectrograph limits
Excitation Wavelengths	514, 532, 633, "785" (782 - 788 nm), 830 nm
Working Distance	7.5 mm (std.), 5.0 or 10 mm optional
Fiber Configuration	Permanently-aligned combination of two single fibers (105 μ m excitation fiber, 200 μ m collection fiber) with filtering and steering micro-optics, N.A. 0.22, in rugged polyurethane jacket.
Filter Efficiency	Patented design for complete filtering of the laser line and quartz spectral contributions from both input and output fibers (O.D. 6 at laser wavelength).
Physical Resistance	Durable probe can be used up to 80°C
Cable Length/ Coupling System	1.5 m with FC (std.) or SMA 905 connectors
Safety Features	Manual safety shutter with integrated calibration standard (patented); Class I sample holders available
Retail Price	\$ 2,750 USD

Specifications and prices are subject to change without notice.